Abstract for the MRS Fall 1995 Meeting, Nov. 27 - Dec. 1, 1995 (Boston, MA). Submitted to Symposium: V

Symposium Title: Scientific Basis for Nuclear Waste Management XIX

A PHENOMENOLOGICAL APPROACH TO SIMULATING THE EVOLUTION OF RADIOACTIVE-WASTE CONTAINER DAMAGE DUE TO PITTING CORROSION[†], <u>Gregory A. Henshall</u>, Lawrence Livermore National Laboratory, Livermore, CA.

The damage to high-level radioactive-waste containers by pitting corrosion is an important repository design consideration. It is desirable to calculate the evolution of the pit depth distribution, not just the time required for initial penetration of the containers, so that the area available for advective or diffusive release of radionuclides through the container can be estimated. A phenomenological approach for computing the time evolution of these distributions is presented which combines elements of the deterministic and stochastic aspects of pit growth. The consistency of this approach with the mechanisms believed to control the evolution of the pit depth distribution is discussed. Qualitative comparisons of the preliminary results with a variety of experimental data from the literature are shown to be generally favorable. The sensitivity of the simulated distributions to changes in the input parameters is discussed. Finally, the results of the current model are compared with those of existing approaches based on extreme value statistics, particularly regarding the extrapolation of laboratory data to long times and large surface areas.

Contact & Presenting Author:

Gregory A. Henshall Lawrence Livermore Labs Chem. & Matls. Sci. Dept. P.O. Box 808, L-355 Livermore CA 94551 (510) 423-4417 FAX: (510) 423-7040

[†] This work was performed under the auspices of the U. S. DOE under contract no. W-7405-ENG-48 at Lawrence Livermore National Laboratory.